

Figure 2

INFORMATION ADMINISTRATOR



- Administrator may add multiple Sites
- Assign Site Administrators for each specific site
- Administrator has the ability to see/change all Site information and configurations
- Site Administrators only have ability to change affiliated Site

- Administrator may add Users to Sites
- Administrator may see all Users in the User Pool
- Site Administrator will only see Users in their Site's User / Groups Pool
- User Pool contains all users from all sites

CREATE & MANAGE SITES

ADD USERS TO SITES




Figure 3




Figure 4





Figure 5





Figure 6

Processes involved in running the icWizard



icWizard uses a 7 step process to create a COM object and interactive HTML user interface.

How the icWizard Works




Figure 7



Figure 8




Figure 9




Figure 10




Figure 11




Figure 12

05842634-091601





Figure 13

Figure 14

BizTalkSchema_ID	Int (Primary Key)		Auto-generated key field
SchemaName	Varchar(30)		User-friendly name for the message
ReqRootTag	Varchar(30)		Root XML Tag name
AckRootTag	Varchar(30)		Root tag for the Ack message
SubMenu_ID	Int		Key of the Sub Menu Item used to secure this request.
DescriptionFile	Varchar(255)		Name of an HTML file describing the message exchange.





You might want to change the `<password>paulcool</password>`

Figure 15

Argument	Type	In/Out	Description
strXML	String	In	XML containing authentication elements.
StrLanguage	String	Out	Name of Language to return messages in (i.e. English). If blank then English is assumed.
StrSiteUrl	String	Out	URL of the site this user is trying to logon to (i.e. intranet.planetci.com).
strUserName	String	Out	User Name of the logon. Must match Login.UserName field in the database to authenticate.
StrPassword	String	Out	Password of the logon in clear text. The AuthenticateLogin object will create an SHA-1 hash of this text and compare it to the Login.Password field in the database to authenticate.
StrResult	String	Out	If failure or error, this will contain the user-friendly text to display to the end user with the failure or error description.
StrErrorMsg	String	Out	If failure or error, this will contain additional error information. If the strOptions /EEXML or /ERXML flags are on, this will be in XML.
StrRootTag	String	Out	Root XML Tag extracted from the document.

Figure 16

Argument	Type	In/Out	Description
strLanguage	String	In	Name of Language to return messages in (i.e. English). If blank then English is assumed.
strSiteUrl	String	In	URL of the site this user is trying to login to (i.e. intranet.planetci.com).
strUserName	String	In	User Name of the login. Must match Login.UserName field in the database to authenticate.
strPassword	String	In	Password of the login in clear text. The AuthenticateLogin object will create an SHA-1 hash of this text and compare it to the Login.Password field in the database to authenticate.
lngLogin_ID	Int	Out	If the authentication is successful, this will contain the Primary key to the login table for the user.
lngProject_ID	Int	Out	If the authentication is successful, this will contain the Primary key to the project table for the strSiteUrl.
lngLanguage_ID	Int	Out	If the authentication is successful, this will contain the Primary key to the Language table for the strLanguage.
strFullName	String	Out	First and Last name of the user.
strEmail	String	Out	Email address of the user.
strResult	String	Out	If failure or error, this will contain the user-friendly text to display to the end user with the failure or error description.
strErrorMsg	String	Out	If failure or error, this will contain additional error information. If the strOptions /EEXML or /ERXML flags are on, this will be in XML.

Figure 17

Argument	Type	In/Out	Description
lngLanguage_Id	Int	In	Name of Language to return messages in (i.e. English). If blank then English is assumed.
lngProject_Id	Int	In	Foreign key for the URL of the site this user is trying to logon to (i.e. intranet.planetci.com).
lngLogin_Id	Int	In	If the authentication is successful, this will contain the Primary key to the login table for the user.
strRootTag	String	In	Root tag that must match FNBizTalkSchema.RootTag field.
strResult	String	Out	If failure or error, this will contain the user-friendly text to display to the end user with the failure or error description.
strErrorMsg	String	Out	If failure or error, this will contain additional error information. If the strOptions /EEXML or /ERXML flags are on, this will be in XML.

Figure 18

Argument	Type	In/Out	Description
lngLanguage_ID	Int	In	Name of Language to return messages in (i.e. English). If blank then English is assumed.
lngProject_ID	Int	In	Foreign key for the URL of the site this user is trying to logon to (i.e. intranet.planetci.com).
lngLogin_ID	Int	In	If the authentication is successful, this will contain the Primary key to the login table for the user.
NdReport	XML DOM	In	XML DOM Object containing the report request.
strResult	String	Out	If failure or error, this will contain the user-friendly text to display to the end user with the failure or error description.
strErrorMsg	String	Out	If failure or error, this will contain additional error information. If the strOptions /EEXML or /ERXML flags are on, this will be in XML.

Figure 19